

Discontinuous galerkin method of the first order parabolic differential equation

Mithun Bala ¹, Dr. Md. Shakhawat Hossain ^{1*}

¹ Department of Mathematics, University of Barishal, Barishal-8254, Bangladesh

*Corresponding author E-mail: mshossain@bu.ac.bd

Abstract

The objective of this paper is to propose a modest numerical error analysis by applying DG finite element method for the parabolic differential equation. The DG method is an imperative numerical method with much mass compensation and more flexible meshing than other numerical methods. The DG method starts by discretizing the domain into a set of non-overlapping elements. This study gives a general introduction and discuss about the discontinuous Galerkin Method of first order parabolic problem. The parabolic problem satisfies the condition of the existence and uniqueness of DG solution. The main goal of this study is to theoretically explore the convergence of the solution of the above methods and show the validity of the results.

Keywords: Galerkin Method; Parabolic Differential Equation; Finite Element Method

1. Introduction

This study provides a theoretical concept to approximate the error of the solutions of a parabolic differential equation. This is focused on the weak formulation of discontinuous Galerkin (DG) method of the first order parabolic problem. Finite element methods (FEM) have been proven valuable in the numerical approximation of solutions to self-adjoint or “nearly” self-adjoint parabolic partial differential equation (PDE) problems and related indefinite PDE systems or to their parabolic counterparts. Possible reasons for the success of FEM are their applicability in very general computational geometries of interest and the availability of tools for their rigorous error analysis. The error analysis is usually based on the variational interpretation of the FEM as a minimization problem over finite-dimensional sets. In 1971, Reed and Hill [1], proposed a new class of FEM, namely the discontinuous Galerkin finite element method for the numerical solution of the nuclear transport PDE problem, which contains a linear first-order hyperbolic PDE. DG methods were first proposed and analyzed in the early 1970s as a technique to numerically solve partial differential equations. The first review of this method was displayed in 1974 by Lesaint and Raviart [2]. By using stronger stability of DG system, this methods was later scrutinized by Johnson, Navert, and J.Pitk’aranta [3], and Johnson and J.Pitk’aranta [4]. The origin of the DG method for parabolic problems cannot be traced back to a single publication as features such as jump penalization in the modern nous were advanced progressively. The comprehensive book by Beatrice Riviere [5], discussed the Discontinuous Galerkin Methods for Solving Elliptic and Parabolic Equations; covered theory, implementation and other information. Jan S. Hesthaven and Tim Warburton [6], has been described Nodal Discontinuous Galerkin Methods; Algorithms, Analysis and also described their applications. P. E. Lewis and J.P. Ward [7], provided a new class of Finite Element Method with its Principles and Application. D.N. Arnoldis [8], presented an interior penalty finite element method with discontinuous elements. R. Becker, P. Hansbo, and M.G. Larson.[9], discussed about energy norm as well as the posteriori error estimation for discontinuous Galerkin methods. B. Cockburn [10], established the Discontinuous Galerkin methods for convection-dominated problems which was existed vast information about discontinuous Galerkin(DG) FEM. B. Cockburn, G.E. Karniadakis, and, C.-W. Shu (eds.) [11], characterized some key element of discontinuous Galerkin(DG) method with its application. Hailiang Liu, Jue Yan [12, 13], initiated another new technique of Discontinuous Galerkin named the Direct Discontinuous Galerkin (DDG) method for Diffusion with Interface Corrections. B. Cockburn, G. E. Karniadakis and C.-W. Shu (eds.) [14] characterized the DG method in the theoretical and computational perception. I. Babu’ska [15] provided particular evidence to apply the Lagrangian multipliers on the finite element method. S. Brenner and L. Scottfor [16] established the essential mathematical analysis and theory of finite element method. B. Cockburn, G. Kanschat, and D. Schötzau [17] signified a novel extent of the DG method by using penalty parameter which is known as the local discontinuous Galerkin (LDG) method.

2. Formulation of the problem

Let Ω be a polygonal domain in $\mathbb{R}^d$, $d = 2$ or 3 . The side of the boundary $\partial\Omega$ of the domain is Γ . Let n be the unit normal vector to the boundary exterior to Ω . For f given in $L^2(\Omega)$, g given in $H^{\frac{1}{2}}(\Gamma)$. Consider the parabolic problem,

$$\nabla \cdot \mathbf{u} + c\mathbf{u} = f \text{ in } \Omega \quad (1)$$

With the boundary condition:

$$\mathbf{u} = g \text{ on } \Gamma \quad (2)$$

Now, let consider a weight function v . Multiplying (1) by v and integrating over the domain Ω , to have,

$$\begin{aligned} (\nabla \cdot \mathbf{u} + c\mathbf{u})v &= fv \\ \Rightarrow (\nabla \cdot \mathbf{u})v + c\mathbf{u}v &= fv \\ \Rightarrow \int_{\Omega} ((\nabla \cdot \mathbf{u})v + c\mathbf{u}v) dx &= \int_{\Omega} fvd x \\ \Rightarrow \int_{\Omega} (\nabla \cdot \mathbf{u})v dx + \int_{\Omega} c\mathbf{u}v dx &= \int_{\Omega} fvd x \\ \Rightarrow \sum \int_{\Omega} (\nabla \cdot \mathbf{u})v dx + \sum \int_{\Omega} c\mathbf{u}v dx &= \sum \int_{\Omega} fvd x \end{aligned} \quad (3)$$

For the proposed DG method, the following DG norm is introduced

$$\|\mathbf{u}\|_{DG}^2 = Ch \|\mathbf{u}\|_{H^s(\Omega)}^2 + Ch_1 \|\mathbf{u}\|_{H^s(\Omega)}^2$$

Using the divergence theorem on every element integral (as v is now elementwise discontinuous), using the anti-clockwise orientation, to get:

$$-\sum \int_{\Omega} ((\nabla \cdot \mathbf{u}) \cdot \nabla v) dx + \sum \int_{\partial\Omega} ((\nabla \cdot \mathbf{u}) \cdot \mathbf{n})v ds + \sum \int_{\Omega} c\mathbf{u}v dx = \int_{\Omega} fvd x$$

Where, $\mathbf{n}$ = The outward normal to each element edge. Then, introduce a bilinear form $B(\mathbf{u}, v)$ as :

$$B(\mathbf{u}, v) = -\int_{\Omega} ((\nabla \cdot \mathbf{u}) \cdot \nabla v) dx + \int_{\partial\Omega} ((\nabla \cdot \mathbf{u}) \cdot \mathbf{n})v ds + \int_{\Omega} c\mathbf{u}v dx$$

Therefore, the DG finite element method is defined as

$$B(\mathbf{u}, v) = \int_{\Omega} fvd x \quad (4)$$

3. Stability analysis

The following theorem is introduced for the stability analysis of this method.

Theorem: Assume that there exist positive constants A and B such that the solution u satisfies the following bounds.

$$B(\mathbf{u}, \mathbf{u}) \leq A \|\mathbf{u}\|_{L^2(\Omega)}^2 + B \|\nabla \cdot \mathbf{u}\|_{L^2(\Omega)}^2$$

Proof: Let, define the bilinear form of the problem:

$$B(\mathbf{u}, v) = -\int_{\Omega} ((\nabla \cdot \mathbf{u}) \cdot \nabla v) dx + \int_{\partial\Omega} ((\nabla \cdot \mathbf{u}) \cdot \mathbf{n})v ds + \int_{\Omega} c\mathbf{u}v dx \quad (5)$$

Putting $v = u$, to obtain,

$$B(\mathbf{u}, \mathbf{u}) = -\int_{\Omega} ((\nabla \cdot \mathbf{u}) \cdot \nabla u) dx + \int_{\partial\Omega} ((\nabla \cdot \mathbf{u}) \cdot \mathbf{n})u ds + \int_{\Omega} cu^2 dx \quad (6)$$

Using Cauchy's inequality on $((\nabla \cdot \mathbf{u}) \cdot \mathbf{n})u$, $\|((\nabla \cdot \mathbf{u}) \cdot \mathbf{n})u\| \leq \|(\nabla \cdot \mathbf{u}) \cdot \mathbf{n}\| \cdot \|u\|$ and,

$$B(\mathbf{u}, \mathbf{u}) \leq -\int_{\Omega} ((\nabla \cdot \mathbf{u}) \cdot \nabla u) dx + \int_{\partial\Omega} ((\nabla \cdot \mathbf{u}) \cdot \mathbf{n})u ds + \int_{\Omega} cu^2 dx \quad (7)$$

Using trace inequality on 2nd term of (3.7),

$$\forall u \in \mathbb{P}_k(\Omega), \forall e \subset \partial\Omega,$$

$$\|(\nabla \cdot \mathbf{u}) \cdot \mathbf{n}\|_{L^2(e)} \leq \tilde{C}_t |e|^{\frac{1}{2}} |\Omega|^{-\frac{1}{2}} \|\nabla \cdot \mathbf{u}\|_{L^2(\Omega)}$$

Also,

$$\forall u \in \mathbb{P}_k(\Omega), \forall e \subset \partial\Omega, \|u\|_{L^2(e)} \leq C_t h_{\Omega}^{-\frac{1}{2}} \|u\|_{L^2(\Omega)}$$

$$\text{It is known that, } \|v\|_{L^2(\Omega)} = \left(\int_{\Omega} v^2 \right)^{\frac{1}{2}}$$

$$\therefore \int_{\Omega} ((\nabla \cdot u) \cdot \nabla u) dx = \|\nabla \cdot u\|_{L^2(\Omega)}^2 \text{ And, } \int_{\Omega} cu^2 dx = c \|u\|_{L^2(\Omega)}^2$$

From the equation (7),

$$B(u, u) = -\|\nabla \cdot u\|_{L^2(\Omega)}^2 + \left(\tilde{C}_t |e|^{\frac{1}{2}} |\Omega|^{-\frac{1}{2}} \|\nabla \cdot u\|_{L^2(\Omega)} \right) \cdot \left(C_t h_{\Omega}^{-\frac{1}{2}} \|u\|_{L^2(\Omega)} \right) + c \|u\|_{L^2(\Omega)}^2 \leq -\|\nabla \cdot u\|_{L^2(\Omega)}^2 + \frac{\epsilon}{2} \left(\tilde{C}_t |e|^{\frac{1}{2}} |\Omega|^{-\frac{1}{2}} \|\nabla \cdot u\|_{L^2(\Omega)} \right)^2 + \frac{1}{2\epsilon} \left(C_t h_{\Omega}^{-\frac{1}{2}} \|u\|_{L^2(\Omega)} \right)^2 + c \|u\|_{L^2(\Omega)}^2$$

So,

$$B(u, u) \leq -\|\nabla \cdot u\|_{L^2(\Omega)}^2 \left\{ 1 - \frac{\epsilon}{2} \left(\tilde{C}_t |e|^{\frac{1}{2}} |\Omega|^{-\frac{1}{2}} \right)^2 \right\} + \|u\|_{L^2(\Omega)}^2 \left\{ \frac{1}{2\epsilon} \left(C_t h_{\Omega}^{-\frac{1}{2}} \right)^2 + c \right\}$$

$$\text{If, consider, } A = \frac{1}{2\epsilon} \left(C_t h_{\Omega}^{-\frac{1}{2}} \right)^2 + c \text{ and } B = -\left(1 - \frac{\epsilon}{2} \left(\tilde{C}_t |e|^{\frac{1}{2}} |\Omega|^{-\frac{1}{2}} \right)^2 \right)$$

Then from the above equation, it is found that,

$$\Rightarrow B(u, u) \leq A \|u\|_{L^2(\Omega)}^2 + B \|\nabla \cdot u\|_{L^2(\Omega)}^2 \quad (8)$$

Hence, this completes the proof.

4. Consistency of the solution

Let consider,

$$\begin{aligned} &\Rightarrow - \int_{\Omega} ((\nabla \cdot u) \cdot \nabla v) dx + \int_{\partial\Omega} ((\nabla \cdot u) \cdot n) v ds + \int_{\Omega} cuv dx = \int_{\Omega} fv dx \\ &\Rightarrow - \int_{\Omega} ((\nabla \cdot u) \cdot \nabla v - cuv) dx + \int_{\partial\Omega} ((\nabla \cdot u) \cdot n) v ds = \int_{\Omega} fv dx \\ &\Rightarrow - \int_{\Omega} ((\nabla \cdot u) \cdot \nabla v - cuv) dx + \int_{\partial\Omega} ((\nabla \cdot u) \cdot n_E) v ds = \int_{\Omega} fv dx \end{aligned} \quad (9)$$

Define, n_E is the outward normal to E. Sum over all elements, switch to the normal vectors n_e ,

$$\begin{aligned} &\sum_{E \in \mathcal{E}_h} \int_{\partial\Omega} ((\nabla \cdot u) \cdot n_E) v ds - \sum_{e \in \partial\Omega} \int_e ((\nabla \cdot u) \cdot n_e) v ds = \sum_{e \in \Gamma_h} \int_e [(\nabla \cdot u) \cdot n_e] v ds \\ &\Rightarrow \sum_{E \in \mathcal{E}_h} \int_{\partial\Omega} ((\nabla \cdot u) \cdot n_E) v ds = \sum_{e \in \partial\Omega} \int_e ((\nabla \cdot u) \cdot n_e) v ds + \sum_{e \in \Gamma_h} \int_e [(\nabla \cdot u) \cdot n_e] v ds \end{aligned}$$

By regularity of the solution u ,

$$(\nabla \cdot u) \cdot n_e = \{(\nabla \cdot u) \cdot n_e\}$$

Substituting all of these values in the equation (3.9), to get,

$$- \sum_{E \in \mathcal{E}_h} \int_{\Omega} ((\nabla \cdot u) \cdot \nabla v - cuv) dx + \sum_{e \in \partial\Omega} \int_e ((\nabla \cdot u) \cdot n_e) v ds + \sum_{e \in \Gamma_h} \int_e \{(\nabla \cdot u) \cdot n_e\} [v] ds = \int_{\Omega} fv dx$$

Subtract, $\epsilon \sum_{e \in \Gamma} \int_e (\nabla v \cdot n_e) u ds$ from both sides and use the Dirichlet boundary condition $u = g$ on Γ ,

$$- \sum_{E \in \mathcal{E}_h} \int_{\Omega} ((\nabla \cdot u) \cdot \nabla v - cuv) dx + \sum_{e \in \partial\Omega} \int_e ((\nabla \cdot u) \cdot n_e) v ds + \sum_{e \in \Gamma_h} \int_e \{(\nabla \cdot u) \cdot n_e\} [v] ds - \epsilon \sum_{e \in \Gamma} \int_e (\nabla v \cdot n_e) u ds = \int_{\Omega} fv dx - \epsilon \sum_{e \in \Gamma} \int_e (\nabla v \cdot n_e) g ds$$

Finally, it can be said that the jumps $[u] = [(\nabla \cdot u) \cdot n_e]$ are zero that is on the interior edges.

Then, clearly have,

$$- \sum_{E \in \mathcal{E}_h} \int_{\Omega} ((\nabla \cdot u) \cdot \nabla v - cuv) dx = \int_{\Omega} fv dx$$

$$\Rightarrow -\sum_{E \in \mathcal{E}_h} \int_{\Omega} ((\nabla \cdot u) \cdot \nabla v) dx + \int_{\Omega} cuv = \int_{\Omega} fv dx$$

which immediately yields in the distributional sense, for all $E \in \mathcal{E}_h$,

$$\nabla \cdot u + cu = f$$

This proves that the given parabolic problem is consistent.

5. Error analysis

The following theorem is proposed for the error estimate of the problem governed by the equation (1).

Theorem: Let u_h be the DG finite element solution and u be the exact solution of (1) arising from (4). Then there exists a constant C such that

$$\|u - u_h\|_{L^2(\Omega)}^2 \leq Ch \|u\|_{DG}^2$$

Proof: Bilinear form of the problem be,

$$B(u, v) = - \int_{\Omega} ((\nabla \cdot u) \cdot \nabla v) dx + \int_{\partial\Omega} ((\nabla \cdot u) \cdot n) v ds + \int_{\Omega} cuv dx \quad (10)$$

Let, the exact solution of the problem be u and the approximation solution be u_h . Putting $u = u_h$ in (10),

$$B(u_h, v) = - \int_{\Omega} ((\nabla \cdot u_h) \cdot \nabla v) dx + \int_{\partial\Omega} ((\nabla \cdot u_h) \cdot n) v ds + \int_{\Omega} cu_h v dx \quad (11)$$

Now,

$$B(u, v) - B(u_h, v) = - \int_{\Omega} ((\nabla \cdot u - \nabla \cdot u_h) \cdot \nabla v) dx + \int_{\partial\Omega} (((\nabla \cdot u) \cdot n) - ((\nabla \cdot u_h) \cdot n)) v ds + \int_{\Omega} c(u - u_h) v dx$$

Let, define, $u = u - u_h$. Then,

$$B(u, u - u_h) - B(u_h, v) = - \int_{\Omega} ((\nabla \cdot u - \nabla \cdot u_h) \cdot \nabla (u - u_h)) dx + \int_{\partial\Omega} (((\nabla \cdot u) \cdot n) - ((\nabla \cdot u_h) \cdot n)) (u - u_h) ds + \int_{\Omega} c(u - u_h) (u - u_h) dx$$

$$\Rightarrow B(u, u - u_h) - B(u_h, v) = - \int_{\Omega} ((\nabla \cdot u - \nabla \cdot u_h) \cdot \nabla (u - u_h)) dx + \int_{\partial\Omega} (((\nabla \cdot u) \cdot n) - ((\nabla \cdot u_h) \cdot n)) (u - u_h) ds + \int_{\Omega} c(u - u_h)^2 dx \quad (12)$$

The first term of right-hand side of the equation (12) can be written as,

$$\begin{aligned} \int_{\Omega} ((\nabla \cdot u - \nabla \cdot u_h) \cdot \nabla (u - u_h)) &= \int_{\Omega} ((\nabla \cdot (u - u_h)) \cdot \nabla (u - u_h)) \\ &= \int_{\Omega} \nabla \cdot (u - u_h)^2 \end{aligned}$$

It is known that, $\int_{\Omega} \nabla \cdot (u - u_h)^2 = \|\nabla \cdot (u - u_h)\|_{L^2(\Omega)}^2$

From the 2nd term of right-hand side of the equation (12),

$$\int_{\partial\Omega} (((\nabla \cdot u) \cdot n) - ((\nabla \cdot u_h) \cdot n)) (u - u_h)$$

Using Cauchy-Schwarz's inequality,

$$|(((\nabla \cdot u) \cdot n) - ((\nabla \cdot u_h) \cdot n))(u - u_h)| \leq \|((\nabla \cdot u) \cdot n) - ((\nabla \cdot u_h) \cdot n)\|_{L^2(\Omega)} \cdot \|u - u_h\|_{L^2(\Omega)}$$

Using Trace inequality,

$$\begin{aligned} \|((\nabla \cdot u) \cdot n) - ((\nabla \cdot u_h) \cdot n)\|_{L^2(\Omega)} &\leq C_t h_{\Omega}^{-\frac{1}{2}} \|\nabla \cdot (u - u_h)\|_{L^2(\Omega)} \\ &\leq C_t h_{\Omega}^{-\frac{1}{2}} \cdot Ch_{\Omega}^{\min(k+1, s)-1} |u|_{H^s(\Omega)} = C_t \cdot Ch_{\Omega}^{-\frac{1}{2} + \min(k+1, s)-1} |u|_{H^s(\Omega)} \end{aligned}$$

Let, $C_t \cdot C = \tilde{C}$. Then,

$$\|((\nabla \cdot u) \cdot n) - ((\nabla \cdot u_h) \cdot n)\|_{L^2(\Omega)} \leq \tilde{C} h_{\Omega}^{\min(k+1,s)-\frac{3}{2}} \|u\|_{H^s(\Omega)}$$

Now, substituting these values in (12),

$$\begin{aligned} B(u - u_h, u - u_h) &\leq -\|\nabla \cdot (u - u_h)\|_{L^2(\Omega)}^2 \\ &+ \left\{ \tilde{C} h_{\Omega}^{\min(k+1,s)-\frac{3}{2}} \|u\|_{H^s(\Omega)} \cdot \|u - u_h\|_{L^2(\Omega)} \right\} + C \|u - u_h\|_{L^2(\Omega)}^2 \end{aligned} \quad (13)$$

Now,

$$\begin{aligned} \|\nabla \cdot (u - u_h)\|_{L^2(\Omega)}^2 &\leq \{C h^{\min(k+1,s)-1} \|u\|_{H^s(\Omega)}\}^2 \\ &= C^2 h^{\min(2k+2,2s)-2} \|u\|_{H^s(\Omega)}^2 \\ &= C h^{\min(2k+2,2s)-2} \|u\|_{H^s(\Omega)}^2 \end{aligned}$$

[By considering the constant C^2 as C]

And

$$\|u - u_h\|_{L^2(\Omega)} \leq C h_{\Omega}^{\min(k+1,s)-2} \|u\|_{H^s(\Omega)}$$

Again,

$$\begin{aligned} \|u - u_h\|_{L^2(\Omega)}^2 &\leq \{C h_{\Omega}^{\min(k+1,s)-2} \|u\|_{L^2(\Omega)}\}^2 \\ &= C^2 h_{\Omega}^{\min(2k+2,2s)-4} \|u\|_{L^2(\Omega)}^2 \\ &= C h_{\Omega}^{\min(2k+2,2s)-4} \|u\|_{L^2(\Omega)}^2 \end{aligned}$$

[By considering the constant C^2 as C]

The last term of right-hand side of the equation (12) can be written as,

$$\int_{\Omega} c(u - u_h)^2 dx = c \|u - u_h\|_{L^2(\Omega)}^2$$

Substituting all of these values in (12),

$$\begin{aligned} B(u - u_h, u - u_h) &\leq -C h_{\Omega}^{\min(2k+2,2s)-2} \|u\|_{H^s(\Omega)}^2 + \left\{ \tilde{C} h_{\Omega}^{\min(k+1,s)-\frac{3}{2}} \|u\|_{H^s(\Omega)} \cdot C h_{\Omega}^{\min(k+1,s)-2} \|u\|_{H^s(\Omega)} \right\} \\ &+ c C h_{\Omega}^{\min(2k+2,2s)-4} \|u\|_{L^2(\Omega)}^2 \\ &\leq \left\{ -C h_{\Omega}^{\min(2k+2,2s)-2} + c C h_{\Omega}^{\min(2k+2,2s)-4} \right\} \|u\|_{L^2(\Omega)}^2 + \left\{ C \tilde{C} h_{\Omega}^{\min(k+1,s)-\frac{3}{2}} \cdot h_{\Omega}^{\min(k+1,s)-2} \right\} \|u\|_{H^s(\Omega)}^2 \\ &\leq C h \|u\|_{H^s(\Omega)}^2 + C h_1 \|u\|_{H^s(\Omega)}^2 \end{aligned} \quad (14)$$

The constant terms is considered as,

$$-C + cC = C \text{ and } C\tilde{C} = C.$$

So, it can be written as :

$$\|u - u_h\|_{L^2(\Omega)}^2 \leq C h \|u\|_{H^s(\Omega)}^2 + C h_1 \|u\|_{H^s(\Omega)}^2$$

By applying proposed DG norm, then

$$\|u - u_h\|_{L^2(\Omega)}^2 \leq C h \|u\|_{DG}^2$$

This completes the proof.

6. Conclusion

The paper investigated the error of the numerical solution by applying the Discontinuous Galerkin finite element method for the first order parabolic differential equation. It is considered discontinuous Galerkin finite element approximations of a model scalar linear parabolic equation. It is a different and straightforward approach to seek error analysis from all other finite element schemes which are given in the literature. The technique used in this paper can also be extended to obtain the $L^2(\Omega)$ error estimate of the time dependent and higher order problems with the optimal order of convergence.

References

- [1] P. Lesaint and T.R. Hill, Triangular mesh methods for the neutron Transport Equation, Technical report, LA-UR-73-479, Los Alamos scientific laboratory, Los Alamos, NM, 1973.
- [2] P. Lesaint and P.-A. Raviart, On a finite element method for solving the neutron transport equation, in Mathematical aspects of finite elements in partial differential equations (Proc. Sympos., Math. Res. Center, Univ. Wisconsin, Madison, Wis., 1974), Math. Res. Center, Univ. of Wisconsin-Madison, Academic Press, New York, 1974, 33, pp. 89123.
- [3] C. Johnson, U. Navert, and J. Pitk'aranta, Finite element methods for linear hyperbolic problems, *Comput. Methods Appl. Mech. Engrg.*, 45 (1984), 285-312. [https://doi.org/10.1016/0045-7825\(84\)90158-0](https://doi.org/10.1016/0045-7825(84)90158-0).
- [4] C. Johnson and J. Pitk'aranta, An analysis of the discontinuous Galerkin method for a scalar hyperbolic equation, *Math. Comp.*, 46 (1986), pp. 1-26. <https://doi.org/10.1090/S0025-5718-1986-0815828-4>.
- [5] Beatrice Riviere, Discontinuous Galerkin Methods for Solving Elliptic and Parabolic Equations; Theory and Implementation, SIAM, January 2008. <https://doi.org/10.1137/1.9780898717440>.
- [6] Hesthaven, J. S., Warburton, T.: Nodal Discontinuous Galerkin Methods: Algorithms, Analysis, and Applications. Ukraine: Springer, 2008, New York. <https://doi.org/10.1007/978-0-387-72067-8>.
- [7] P. E. Lewis and J.P. Ward, The Finite Element Method; Principles and Application; Addition – Wesley, 1991.
- [8] D.N. Arnold: An interior penalty finite element method with discontinuous elements." *SIAM J. Numer. Anal.* 19, 1982, 742–760. <https://doi.org/10.1137/0719052>.
- [9] R. Becker, P. Hansbo, and M.G. Larson: "Energy norm a posteriori error estimation for discontinuous Galerkin methods." *Comput. Methods Appl. Mech. Engrg.* 192, 2003, 723–733. [https://doi.org/10.1016/S0045-7825\(02\)00593-5](https://doi.org/10.1016/S0045-7825(02)00593-5).
- [10] B. Cockburn: Discontinuous Galerkin methods for convection-dominated problems." In: High-order Methods for Computational Physics, Springer, Berlin, 1999, 69-224. https://doi.org/10.1007/978-3-662-03882-6_2.
- [11] B. Cockburn, G.E. Karniadakis, and C.-W. Shu (eds.): Discontinuous Galerkin Methods.' Theory, computation and applications. Papers from the 1st International Symposium held in Newport, RI, May 24–26, 1999. SpringerVerlag, Berlin, 2000. <https://doi.org/10.1007/978-3-642-59721-3>.
- [12] Hailiang Liu, Jue Yan, The Direct Discontinuous Galerkin (DDG) Methods for Diffusion Problems, *SIAM J. NUMER. ANAL.* Vol. 47, No. 1, pp. 675–698. <https://doi.org/10.1137/080720255>.
- [13] Hailiang Liu, Jue Yan, The Direct Discontinuous Galerkin (DDG) Method for Diffusion with Interface Corrections, *Commun. Comput. Phys.* Vol. 8, No. 3, pp. 541-564 <https://doi.org/10.4208/cicp.010909.011209a>.
- [14] B. Cockburn, G. E. Karniadakis and C.-W. Shu (eds.), Discontinuous Galerkin methods. Theory, computation and applications, Lecture Notes in Computational Science and Engineering, 11. Springer-Verlag, Berlin, 2000. <https://doi.org/10.1007/978-3-642-59721-3>.
- [15] I. Babu'ska, The finite element method with Lagrangian multipliers, *Numerische Mathematik*, 20 (1973), pp. 179–192. <https://doi.org/10.1007/BF01436561>.
- [16] S. Brenner and L. Scott, The Mathematical Theory of Finite Element Methods, Springer-Verlag, New York, 1994. <https://doi.org/10.1007/978-1-4757-4338-8>.
- [17] B. Cockburn, G. Kanschat, and D. Schötzau, The local discontinuous Galerkin method for the Oseen equations, *Mathematics of Computation*, 73 (2003), pp. 569–593. <https://doi.org/10.1090/S0025-5718-03-01552-7>.