



# A dependable smart security system for dominant attacks on agriculture crop fields

P.Visu<sup>1\*</sup>, V. Muruganathan<sup>2</sup>

<sup>1</sup>Associate Professor, Department of IT, Velammal Engineering College, Chennai, India.

<sup>2</sup>Lecturer, SEEMIT, Institute Technology Pertama, Mantin, Negeri Sembilan, Malaysia.

\*Corresponding author E-mail: [pandu.visu@gmail.com](mailto:pandu.visu@gmail.com)

## Abstract

This study is around recognition of unapproved access to a nation inhabitant's crop field when the rancher is remote from the entrance of his field. Here we outline a dependable keen enacted security framework with the assistance of sensor innovation to change the ways of life and gives a superior route to the issues wherever looked via landowners in their day by day life. By utilizing basic electronic segments nature, it is more versatile and financially savvy. The model is separated into three units; the power supply unit which utilizes the utilization of DC battery and mains supply for the use of continuous power supply to the circuit, the trigger unit for enacting the caution unit and intended to have much time and period and direct affectability to lessen rate of false caution, and the caution sufficiency unit which fundamental capacity is to deliver adequacy alert sound when activated by the trigger unit that creating a substantial capable of being heard sound which can alarm the whole neighbourhood or drive an interloper off. The model planned by thinking about economy, accessibility of parts and research materials, effectiveness, similarity and accommodation and furthermore toughness in the outline procedure this framework deals with the guideline of touch sensor. The general framework was developed and tried in such a path by upgrading the execution in each period of the sensor is rudimented over the capitulated irregularity of the circuits assume control over the vital working instrument for the alert to capacity to work legitimately. Working Principle is based on Weidem's Sensor where all the chips and ICs connected over the soldered board has to satisfy the rules with cumulative actions for the sensor to work together when an object would step onto the pressure sensitive board, will be augmented.

**Keywords:** Sensors, Automation, Control System, Electronic Circuit, Maximum Power Transfer.

## 1. Introduction

Land debasement is a procedure in which the estimation of the earth is influenced by a mix of human and creatures following up on the land. It is seen as any change or aggravation to the land apparent to be pernicious or unwanted[1]. Normal dangers are prohibited as a reason; however human exercises can by implication influence marvels, for example, surges and shrubbery fires. These offered ascend to the requirement for improvement in the innovation of caution frameworks which uses different standards, for example, infrared movement recognition, light (photograph) touchy electronic gadgets et cetera. Indeed, even with the presentation of these caution frameworks which have lessened enormously the level of uncertainty, there is as yet an issue of false alert which should be limited[2]. With a specific end goal to successfully diminish the level of uncertainty and stay away from false cautions which can make pointless turmoil, a touch actuated security framework is required[3]. This framework if appropriately planned will give security and guarantee cautions are initiated just when an unapproved individual attempt to access the ensured territory or gadget by touching the passageway or some other piece of the gadget.

## 2. Alarms and Sensors

The growing progressions in science and advancement have offered rise to an epic change in the innovation of alert sensors.

These sensors go about as information sources which triggers the alert[4]. A portion of the alert sensor innovations that have advanced throughout the years are.

The alert sensor innovation utilized in this framework is the capacitance sensor. The sensor's wire is typically joined to metallic entryway handles, metallic, and defenders and so on. It typically require touch or closeness and resulting adjustment of capacitance to trigger the alert. This sensor compose received in this framework helps in the lessening of false activating of cautions and the identification of gatecrashers isn't in any capacity influenced by climate condition, radio recurrence or electromagnetic aggravation[5].

The issue of incessant power blackouts in some piece of the world today offered ascend to the utilization of a programmed control change over switch which has the capacity of exchanging between the mains supply and DC battery utilizing a hand-off. This gives an inactive (or standby) repetition for the power supply to the alert framework subsequently expanding its dependability[6]. The framework has both security application and extravagance, since it is more agreeable and simple for a gatecrasher to be naturally recognized.

The prominent alarms are used when under threat to send alarm signals to specific locations and the types of these alarm systems are:

- (i) **Identification alarm.**
- (ii) **Panic button alarm (schools, banks, offices).**



### 3. System design and implementation

In this segment will talk about the design procedure and the basic theory of components used for this work. The section is further divided into two sub-sections as design theory and system design analysis[7].

**The Stages of execution are,**

The system design was implemented in three units as shown in Fig. 1. These units are:

- (A) The power supply unit
- (B) The trigger unit
- (C) The alarm/amplifier units

These types of electronic pressure sensors generally use a force collectors such as,

1. Diaphragm
2. Piston
3. Bourdon tube
4. Bellows, to measure strain (or deflection) due to applied force over the area.

**Organization of Paper**

This paper focus on the review of micro machined MEMS capacitive principle pressure sensor. It is vital to select material for MEMS fabrication. Section II explains material and their properties for structural and packaging material used in the fabrication of MEMS capacitive pressure sensor. The principle of capacitive pressure sensor with various mode of operation is explained in section III. It also covers electrostatic and piezoelectrically tuned capacitive pressure sensor. Section IV explains acoustic pressure sensor using capacitive principle.


Various micro machining technique used in the fabrication of capacitive pressure sensor was also discussed in section V. This section discussed the fabrication technique adopted in the fabrication of silicon diaphragm, ceramic diaphragm for high temperature application and polymer diaphragm for high sensitivity, condenser microphone was also discussed.

**Case Organization**


Silicon and silicon mixes are broadly utilized as a part of the manufacture of smaller scale weight sensor. As of late the use of polymer material has expanded because of different preferences like basic steadiness, more adaptable, great electrical and warm qualities with a constraint in high temperature application.

Capacitive weight sensors are intended to gauge outright weight are talked about in the references. The decided from this change in capacitance. structure has chamber with a reference weight (supreme weight <1mTorr) is cut off by a versatile film that is presented to an outrageous weight. Together with the inverse side of this chamber, the electrically conductive layer frames parallel plates of capacitive sensor. The stomach film is distorted because of the weight contrast between the outer weight and the interior reference weight. The capacitance of this capacitor changes because of the variable separation between the layer and the rear of the chamber go about as a co-working terminal[8].

The circuit and board representations of the touch/pressure analyser circuit are depicted below.



**Fig:1** Touch activated security system against the crop attack.



**Fig:2** The circuit diagram of the Touch Sensor Mechanism embalming the working different electronic devices

**Methodology**

Execution is made by an entertainment structure, which takes any sensor topology and any game plan of 2D shapes as data, exhibited in SVG records. To speak to the necessities recorded above,the framework thusly scales, moves and rotates these shapes to duplicate a gigantic combination of cut-out shapes over the entire sensor sheet . As an execution file, it figures the normal extent of the region on the cut-out that remaining parts touch-intuitive[9]. We recreate a sensor sheet with 266 x 266 mm, secured with a rectangular cluster of 26 x 26 terminals, each measured 10 x 10 mm and separated with 0.25 mm remove.

We reenact the accompanying topologies: network as the standard (G), star (S), tree (T), overlaid star and tree (ST), overlaid tree and tree turned by 90° around the middle point (TT), and additionally overlaid star, tree and pivoted tree (STT)[10]. Notwithstanding the reenactment of a multi-touch sheet that can be produced with mechanical hardware, we additionally recreated the models that we have assembled, utilizing the measurements and topologies presented before in this paper.

**The hotness reimbursement**

At the point when a power is connected to the pillar, its upper surface encounters an extending, relating negative distortion, while the lower surface is packed and encounters positive misshapening, yet the twisting of the upper and lower surfaces is equivalent in outright esteem. Along these lines, when two FBGs with a similar temperature affectability coefficient are stuck on the upper and lower surfaces of the bar, individually, the wavelength movements of the two gratings alter to the contrary course with an indistinguishable estimation of the movements[11]. It ought to be called attention to that two fiber gratings are situated in a similar

temperature condition, and the contrast between the movements of two gratings will be kept unaltered, despite the fact that the difference in the temperature may cause an individual move for each grinding. That implies the temperature impact on the grinding is wiped out and the grinding gets a pay in the predetermined temperature.

To get the ideal parameters of the stomach and to check the consistency of the stomach plan with the genuine case, we embraced ANSYS 14.0 (ANSYS Inc., Pittsburgh, PA, USA) to reenact the weight stomach. ANSYS is a general investigation programming in view of the limited component technique which enables us to do the investigation of the structure with warm, stable, liquid and electromagnetic fields[12].

The 1:1-scale three-dimensional (3D) model of the versatile ridged stomach is transported in into the ANSYS at to start with, as appeared. The distance across of the full-estimate stomach is 100 mm, and the crease compose is picked as "triangle waveform" (6 rings) with a groove profundity of 2 mm.

The recreation comes about show an exchange off between the thickness of the stomach and the estimation run. At the point when the stomach is thick, the affectability of the stomach is low, which prompts an extended scope of estimation with a lower determination. At the point when the stomach is too thin, notwithstanding the upgraded affectability, the estimation go is diminished and brings about a debasement in continuance to the effect of a high weight distinction, notwithstanding bringing about harm to the stomach. As indicated by the estimation range and determination, we picked a stomach that is 0.15 mm thick to manufacture and lead tests. It introduces the genuine photo of the sensor[13].

Autonomous weight creating gadgets should be utilized for the most part: one delivers high weight and alternate delivers low weight in the meantime. In any case, in this test, we just utilized one generator to give high weight, while the low weight was settled to disentangle the test framework. It was anything but difficult to create differential weight going from 0 to 10 kPa.

## 4. Conclusion

In Along these lines by interfacing an intensifier circuit on fencing, if fencing circuit is grounded by touching it to the creature then our system will be initiated. Bell will be enacted and by utilizing LDR it distinguishes light force, on the off chance that it is less, it will focus the light. With the goal that wild creatures won't go into the homestead. It will flee. GSM module sends message to the agriculturist to alarm him, after the enactment of framework. From this it is presumed that the plan framework is extremely valuable and reasonable to the rancher. The outline framework won't be hazardous to creature and human being, and it ensures cultivate. Later on, there will be huge degree, this task can be influenced in light of image handling in which wild creature to can identify by cameras and on the off chance that it comes towards cultivate then framework will be specifically actuated through remote systems. Wild creatures can likewise be detected by utilizing remote systems, for example, laser remote sensors and by detecting this laser or sensor's security framework will be actuated.

## References

- [1] S. R. Nandurkar, V. R. Thool, R. C. Thool, "Design and Development of Precision Agriculture System Using Wireless Sensor Network", IEEE International Conference on Automation, Control, Energy and Systems (ACES), 2014.
- [2] Joaquín Gutiérrez, Juan Francisco Villa-Medina, Alejandra Nieto-Garibay, and Miguel Ángel Porta-Gándara, "Automated Irrigation System Using a Wireless Sensor Network and GPRS Module", IEEE transactions on instrumentation and measurement, 0018-9456, 2013.
- [3] Dr. V. Vidya Devi, G. Meena Kumari, "Real-Time Automation and Monitoring System for Modernized Agriculture", International Journal of Review and Research in Applied Sciences and Engineering (IJRRASE) Vol3 No.1. PP 7-12, 2013.
- [4] Y. Kim, R. Evans and W. Iversen, "Remote Sensing and Control of an Irrigation System Using a Distributed Wireless Sensor Network", IEEE Transactions on Instrumentation and Measurement, pp. 1379-1387, 2008.
- [5] Hayes, J.; Crowley, K.; Diamond, D. Simultaneous web-based real-time temperature monitoring using multiple wireless sensor networks. Sensors IEEE, October 30-November 3, p. 4, 2005.
- [6] Q. Wang, A. Terzis and A. Szalay, "A Novel Soil Measuring Wireless Sensor Network", IEEE Transactions on Instrumentation and Measurement, pp. 412-415, 2010.
- [7] Yoo, S.; Kim, J.; Kim, T.; Ahn, S.; Sung, J.; Kim, D. A2S: Automated agriculture system based on WSN. In ISCE 2007. IEEE International Symposium on Consumer Electronics, 2007, Irving, TX, USA, 2007.
- [8] Arampatzis, T.; Lygeros, J.; Manesis, S. A survey of applications of wireless sensors and Wireless Sensor Networks. In 2005 IEEE International Symposium on Intelligent Control & 13th Mediterranean Conference on Control and Automation. Limassol, Cyprus, 1-2, 719-724 2005.
- [9] Orazio Mirabella and Michele Brischetto, 2011. "A Hybrid Wired/Wireless Networking Infrastructure for Greenhouse Management", IEEE transactions on instrumentation and measurement, vol. 60, no. 2, pp 398-407.
- [10] N. Kotamaki and S. Thessler and J. Koskiahio and A. O. Hannukkala and H. Huitu and T. Huttula and J. Havento and M. Jarvenpaa (2009). "Wireless in-situ sensor network for agriculture and water monitoring on a river basin scale in Southern Finland: evaluation from a data users perspective". Sensors 4, 9: 2862-2883. doi:10.3390/s90402862 2009.
- [11] Liu, H.; Meng, Z.; Cui, S. A wireless sensor network prototype for environmental monitoring in greenhouses. International Conference on Wireless Communications, Networking and Mobile Computing (WiCom 2007), Shanghai, China; 21-25 September 2007.
- [12] Baker, N. ZigBee and bluetooth - Strengths and weaknesses for industrial applications. Comput. Control. Eng. 2005, 16, 20-25.
- [13] IEEE, Wireless medium access control (MAC) and physical layer (PHY) specifications for low rate wireless personal area networks (LRWPANs). In The Institute of Electrical and Electronics Engineers Inc.: New York, NY, USA, 2003